

BYK-P 9912

Processing additive with internal release properties for unfilled, filled and fiber-reinforced polyurethane systems.

Product Data

Composition

Combination of surface-active substances

Typical Properties

The values indicated in this data sheet describe typical properties and do not constitute specification limits.

Density at 20 °C:	0.9500 g/cm ³
Refractive index n _{20/D} :	1.472
Non-volatile matter (10 min., 150 °C):	> 99 %
Flash point:	> 110 °C

Food Contact Legal Status

For the current food contact legal status, please contact our product safety department or visit www.byk.com for further information.

Applications


Ambient Curing Systems

Special Features and Benefits

BYK-P 9912 is liquid and was specifically developed for use as processing additives in polyurethane systems. Due to additional internal mold release properties, it accelerates the production process by significantly reducing the time that the mold is idle. BYK-P 9912 has no negative impact on processing parameters such as viscosity and reactivity. No negative influence on the mechanical properties of the finished component could be observed.

Recommended Use

Unfilled, filled and fiber-reinforced polyurethane systems	
--	---

 especially recommended

Recommended Levels

2-3 % additive (as supplied) based on the total formulation (polyol and isocyanate).

The above recommended levels can be used for orientation. Optimal levels are determined through a series of laboratory tests.

Incorporation and Processing Instructions

BYK-P 9912 can be added directly to the polyol or isocyanate components. Incorporating the additive in the polyol components at an early stage, before other raw materials, is particularly recommended. It is also possible to dose the additive into the pre-mixed system. A thorough and homogeneous distribution of the additive is necessary to achieve the best possible mold release.



Additive Guide



BYK-Chemie GmbH
P.O. Box 10 02 45
46462 Wesel
Germany
Tel +49 281 670-0
Fax +49 281 65735

info@byk.com
www.byk.com

ANTI-TERRA®, BYK®, BYK®-DYNWET®, BYK®-SILCLEAN®, BYKANOL®, BYKETOL®, BYKJET®, BYKOPLAST®, BYKUMEN®, CARBOBYK®, DISPERBYK®, DISPERPLAST®, LACTIMON®, NANOBYK®, PAPERBYK®, SILBYK®, VISCOBYK®, and Greenability® are registered trademarks of BYK-Chemie. ACTAL®, ADJUST®, ADVITROL®, ASTRABEN®, BENTOLITE®, CLAYTONE®, CLOISITE®, FULACOLOR®, FULCAT®, GARAMITE®, GELWHITE®, LAPONITE®, MINERAL COLLOID®, OPTIBENT®, OPTIFLO®, OPTIGEL®, PURE THIX®, RHEOCIN®, RHEOTIX®, RIC-SYN®, TIXOGEL®, and VISCOSEAL® are registered trademarks of BYK Additives. AQUACER®, AQUAMAT®, AQUATIX®, CERACOL®, CERAFAK®, CERAFLOUR®, CERAMAT®, CERATIX®, HORDAMER®, and MINERPOL® are registered trademarks of BYK-Cera. SCONA® is a registered trademark of BYK Kometra.

The information herein is based on our present knowledge and experience. The information merely describes the properties of our products but no guarantee of properties in the legal sense shall be implied. We recommend testing our products as to their suitability for your envisaged purpose prior to use. No warranties of any kind, either express or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding any products mentioned herein and data or information set forth, or that such products, data or information may be used without infringing intellectual property rights of third parties. We reserve the right to make any changes according to technological progress or further developments.

This issue replaces all previous versions – Printed in Germany