



# WESTLAKE PVC CORPORATION

WESTLAKE PVC CORP.  
2801 POST OAK BLVD.  
HOUSTON, TX 77056

PHONE: (888) 277-3072  
FAX: (713) 963-1562

## 1185

**Westlake PVC 1185** PVC resin is a low molecular weight resin with excellent clarity designed for applications such as blow molding or where high plasticizer uptake is required. The excellent heat stability, clarity, cleanliness and uniformity of this product make it well suited for a broad range of applications.

### Suggested Applications

**Westlake PVC 1185** PVC resin is typically used in production of bottles, highly plasticized and injection molded products.

### TYPICAL PROPERTIES

Appearance (Visual Observation)	Free Flowing White Powder
K-value	56
Inherent Viscosity (ASTM D5225)	0.68
Relative Viscosity	1.85
Volatiles (% maximum)	0.2
Bulk Density (g/cc) (ASTM D1895)	0.53
Particle Size (ASTM D1921)	
Through 40 mesh (% minimum)	99.9
Through 200 mesh (% maximum)	7.0
ASTM Cell Classification (ASTM D1755)	GP1-16050

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required.