



# WESTLAKE PVC CORPORATION

WESTLAKE PVC CORP.  
2801 POST OAK BLVD.  
HOUSTON, TX 77056

PHONE: (888) 277-3072  
FAX: (713) 963-1562

## 1195

**Westlake PVC 1195** PVC resin is a low molecular weight resin designed for rigid injection molding, calendaring, sheet extrusion, and blow molding.

### Suggested Applications

**Westlake PVC 1195** PVC resin is well suited for a broad range of applications. Typical applications include pipe fittings and other injection molded products, calendered film and sheet, extruded sheet, bottles, and plasticized applications.

### TYPICAL PROPERTIES

Appearance (Visual Observation)	Free Flowing White Powder
K-value	58
Inherent Viscosity (ASTM D5225)	0.73
Relative Viscosity	1.90
Volatiles (% maximum)	0.2
Bulk Density (g/cc) (ASTM D1895)	0.53
Particle Size (ASTM D1921)	
Through 40 mesh (% minimum)	99.9
Through 200 mesh (% maximum)	7.0
ASTM Cell Classification (ASTM D1755)	GP2-16050

All statements, information and data given herein are believed to be accurate and reliable but are presented without guaranty, warranty, or responsibility of any kind, expressed or implied. Statements or suggestions concerning possible use of our products are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe any patent. The user should not assume that all safety measures are indicated or that other measures may not be required.